



ADVAN A005 (Slick)



ADVAN A006 (Wet)

Dimension	Felgen	Abroll Umfang	Mischung	CHF
13 Zoll				
200/555R13	8.5 – 10"	1746	S (diagonal)	320.–
200/50R13	7.5 – 9"	1751	S	310.–
240/45R13	9 – 10.5"	1820	S	330.–
14 Zoll				
180/530R14	5 – 7.5"	1643	S, H	300.–
15 Zoll				
190/560R15	6 – 7.5"	1736	S, H, WET	330.–
190/580R15	6 – 7.5"	1798	S, H, WET	340.–
16 Zoll				
190/580R16	5.5 – 7.5"	1798	S, H, WET	370.–
210/580R16	6.5 – 8"	1798	S, H	400.–
230/630R16	7 – 9"	1953	H	440.–
17 Zoll				
210/610R17	6.5 – 8.5"	1915	S, H	420.–
210/625R17	7.5 – 8.5"	1937	WET	440.–
230/610R17	7 – 9"	1915	S, M, H, WET	450.–
230/625R17	7 – 9"	1937	S, H	470.–
240/640R17	9 – 10"	1985	S, H, WET	490.–
260/640R17	9 – 10.5"	1985	H, WET	490.–
18 Zoll				
210/650R18	7.5" – 9"	2015	S, H	480.–
230/650R18	7 – 9"	2015	SS, S, M, H, WET	490.–
250/650R18	8 – 10"	2015	SS, S, M, H, WET	530.–
280/650R18	9 – 11"	2015	SS, S, M, H, WET	540.–
280/680R18	10 – 12"	2108	M, H, WET	570.–
320/650R18	10.5 – 12.5"	2018	SS, S, M, H, WET	640.–
330/710R18	11 – 14"	2201	S, SS, WET	650.–

Für genaue Angaben zu Luftdruck und Sturzweiten setzen Sie sich bitte mit YOKOBO AG in Verbindung.